

HYDRAULIC GRAPPLE

HYDRAULIC MATERIAL/STONE GRAPPLE

Excavator Attachment



Product Features

- ※Wide opening width with light weight , not only outstanding performance in handing the iron bar but also maximize the operation efficiency with light weight.
- ※Unlimited clockwise and anti-clockwise 360 rotatable.
- ※ Special designed swing bearing for durability and big cylinder for more power.
- ※ Check valve is embedded for better safety shock value enclosed for better safety from damage.
- ※Wear resistant special solid steel is used and no extra reinforcement is requirement.
- ※Flexible choices dependent on job environment Operator can control the rotating speed. Versatile applications including handing of stones, wood, cane, pipes,disposable waste, landscaping works and many others.



HYDRAULIC MATERIAL



HYDRAULIC GRAPPLE

Product Parameters

Name \ Model	Unit	BYKL 02	BYKL 04	BYKL 06	BYKL 08	BYKL 10	BYKL 14	BYKL 20
Weight	Kg	300	390	740	1380	1700	1900	2100
Max jaw opening	M/m	1060	1400	1800	2300	2500	2500	2700
Oil Pressure	kg/cm2	110-140	120-160	150-170	160-180	160-180	180-200	180-200
Operating flux	kg/cm2	160	180	190	200	210	250	250
Cylinder Volume	L/min	20-40	50-100	90-110	100-140	130-170	200-250	250-320
Suitable excavator	Ton	2×2	4.5×2	8.0×2	9.7×2	12×2	12×2	14×2
Applicable Excavator	Ton	1.5-6	7-11	12-16	17-23	24-30	31-40	41-50